

Test Verification of Conformity

In the basis of the tests undertaken, the sample(s) of the below product have been found to comply with the requirements of the referenced specifications at the time the tests were carried out.

Applicant Name & Address:	Shenzhen SOFARSOLAR Co., Ltd. 5/F, Building 4, Antongda Industrial Park, No.1 Liuxian Avenue, Xin'an Street, Bao'an District, Shenzhen City, Guangdong Province, P.R.China
Product Description:	Solar inverter
Ratings & Principle Characteristics:	See Annex to Test Verification of Conformity
Models:	SOFAR 4.4KTL-X, SOFAR 5.5KTL-X, SOFAR 6.6KTL-X, SOFAR 8.8KTL-X, SOFAR 11KTL-X
Brand Name:	
Relevant Standards	Engineering Recommendation G83 Issue 2 (December 2012) Recommendations For The Connection Of Type Tested Small-Scale Embedded Generators (Up To 16A Per Phase) In Parallel With Low-Voltage Distribution Systems
Verification Issuing Office:	Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Date of Tests:	18 April 2017 – 14 Jul., 2017
Test Report Number(s):	170418011GZU-001

This verification is part of the full test report(s) and should be read in conjunction with them.

Signature 
Name: Grady Ye
Position: Assistant Manager
Date: 19 July 2017


This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Annex to Test Verification of Conformity

This is an Annex to Test Verification of Conformity with Verification/Report Number(s):
170418011GZU-001. the issuing office is Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
(Address: Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD,
Guangzhou, China).

Ratings & Principle Characteristics:

Maximum d.c. input voltage: 1000 Vdc
Input voltage range: 160-960 Vdc
MPPT voltage range (full Load): 190-850 V (for SOFAR 4.4KTL-X); 240-850 V(for SOFAR 5.5KTL-X); 290-850 V(for SOFAR 6.6KTL-X); 380-850 V(for SOFAR 8.8KTL-X); 480-850 V(for SOFAR 11KTL-X);
Max. input current: 2×11 A
Nominal output voltage: 3/N/PE230V/400Vac
Max. output current: 3×6.4 A (for SOFAR 4.4KTL-X); 3×8.0 A (for SOFAR 5.5KTL-X); 3×9.6 A (for SOFAR 6.6KTL-X); 3×12.8A (for SOFAR 8.8KTL-X); 3×15.9 A (for SOFAR 11KTL-X);
Nominal frequency: 50 Hz
Max. output power: 4400VA (for SOFAR 4.4KTL-X); 5500VA (for SOFAR 5.5KTL-X); 6600VA (for SOFAR 6.6KTL-X); 8800VA(for SOFAR 8.8KTL-X); 11000VA (for SOFAR 11KTL-X);
Power Factor: 0.8 Leading – 0.8 Lagging
Ingress protection: IP65
Operating temperature range: -25~+60°C

Signature

Name: Grady Ye
Position: Assistant Manager
Date: 19 July 2017



This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.