

VERIFICATION OF COMPLIANCE

No.: GZES2101000454PV02


Applicant: Shenzhen SOFARSOLAR Co., Ltd.
401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen SOFARSOLAR Co., Ltd.
401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China

Product Name: Solar Grid-tied Inverter

Product Description: Inverter used in PV system

Model No.: SOFAR 3.3KTL-X; SOFAR 4.4KTL-X;
SOFAR 5KTL-X; SOFAR 5.5KTL-X; SOFAR 6.6KTL-X;
SOFAR 8.8KTL-X; SOFAR 11KTL-X; SOFAR 12KTL-X;

Trade Mark: 

Rating: Refer to page 2

Intended Use: PV System

Protection against Electric Shock: Class I

Additional Information (if any): IP 65

Firmware version: V2.8

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: ENA Engineering Recommendation G99 Issue 1 Amendment 3
May 2018

as shown in the

Test Report Number(s): GZES210100045402

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.


David Guo
Senior Technical Manager
SGS-CSTC



2021-02-09

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)

No.:

GZES2101000454PV02

Other information added :
Ratings

Model Number	SOFAR 3.3KTL-X	SOFAR 4.4KTL-X	SOFAR 5KTL-X	SOFAR 5.5KTL-X
Input (DC)				
Max. input voltage	1000 V			
Start-up voltage	200 V			
Operating MPPT voltage range	160~960V			
Max. input MPPT current	11A/11A			
Full power MPPT voltage range	160~850V	190~850V	240~850V	240~850V
Max. Input power	4390W	5860W	6650W	7320W
Output (AC)				
Rated grid voltage	3/N/PE, 230/400V			
Rated grid frequency	50Hz			
Rated output current	3 x 4.3A	3 x 5.8A	3 x 7.2A	3 x 7.2A
Max. output current	3 x 4.8A	3 x 6.4A	3 x 8.0A	3 x 8.0A
Rated output power	3000W	4000W	5000W	5000W
Max. output power	3300VA	4400VA	5000VA	5500VA
Power factor	1 (adjustable+/-0.8)			
Ambient temperature range	-25 °C ~60 °C			
Ingress protection	IP65			
Protective class	Class I			

Model Number	SOFAR 6.6KTL-X	SOFAR 8.8KTL-X	SOFAR 11KTL-X	SOFAR 12KTL-X
Input (DC)				
Max. input voltage	1000 V			
Start-up voltage	200 V			
Operating MPPT voltage range	160~960V			
Max. input MPPT current	11A/11A			
Full power MPPT voltage range	290~850V	380~850V	480~850V	575~850V
Max. Input power	8780W	11710W	15960W	8780W
Output (AC)				
Rated grid voltage	3/N/PE, 230/400V			
Rated grid frequency	50Hz			
Rated output current	3 x 8.7A	3 x 11.6A	3 x 14.5A	3 x 17.4A
Max. output current	3 x 9.6A	3 x 12.8A	3 x 15.9A	3 x 19.1A
Rated output power	6000W	8000W	10000W	12000W
Max. output power	6600VA	8800VA	11000VA	13200VA
Power factor	1 (adjustable+/-0.8)			
Ambient temperature range	-25 °C ~60 °C			
Ingress protection	IP65			
Protective class	Class I			

David Guo

Senior Technical Manager
SGS-CSTC

2021-02-09

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)