

VERIFICATION OF COMPLIANCE

No.: GZES2105019406PV

Applicant: Shenzhen SOFARSOLAR Co., Ltd.
401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen SOFARSOLAR Co., Ltd.
401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China

Product Name: Solar Grid-tied Inverter (Single Phase)

Product Description: Inverter used in PV system

Model No.: SOFAR 7KTLM-G3, SOFAR 7.7KTLM-G3, SOFAR 8KTLM-G3, SOFAR 9KTLM-G3, SOFAR 10KTLM-G3, SOFAR 10.5KTLM-G.

Trade Mark:



Rating:

Refer to page 2

Intended Use:

PV System

Protection against Electric Shock:

Class I

Additional Information (if any):

Software Version: V000001

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard:

ENA Engineering Recommendation G99 Issue 1 Amendment 6
09 March 2020

as shown in the

Test Report Number(s):

GZES210501940601

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

David Guo

Senior Technical Manager
SGS-CSTC

2021-07-01

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)

No.: GZES2105019406PV

Other information added :

Rating:

Model Number	SOFAR 7KTLM -G3	SOFAR 7.7KTLM -G3	SOFAR 8KTLM -G3	SOFAR 9KTLM -G3	SOFAR 10KTLM -G3	SOFAR 10.5KTLM -G3
Input (DC)						
Max. input power	10500 W	10500 W	12000 W	13500 W	15000 W	15000 W
Max. input voltage	600 V					
Start-up voltage	90 V					
Rated input voltage	360 V					
MPPT operating voltage range	80V~550 V					
Full power MPPT voltage range	200 V~ 500 V	200 V~ 500 V	230 V~ 500 V	260 V~ 500 V	280 V~ 500 V	300 V~ 500 V
Max. input MPPT current	20A/16A/16A					
Output (AC)						
Rated power	7000 W	7700 W	8000 W	9000 W	10000 W	10500 W
Max. AC power	7700 VA	7700 VA	8800 VA	9900 VA	10000 VA	10500 VA
Nominal output current	31.8 A	35 A	36.4 A	40.9 A	45.5 A	45.6 A
Max output current	35 A	35 A	40 A	45 A	46 A	46 A
Nominal grid voltage	L/N/PE, 230 Vac					
Nominal frequency	50 Hz					
Power factor	1 default (adjustable+/-0.8)					
Ambient temperature range	-30 °C ~65 °C					
Degree of protection	IP65					
Protective Class	Class I					




David Guo
Senior Technical Manager
SGS-CSTC

2021-07-01

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)