PowerAll

8 / 10 / 12 kW
5 / 10 / 15 / 20 / 25 / 30 kWh

Single-phase All-in-one ESS



- SOFAR Hybrid inverter
- SOFAR Battery

We've GOT YOU COVERED with CGL insurance.

User-friendly

- Easy installation & extendable capacity
- Modular and stacking integrated design

Flexible applications


- Multi-function EMS integrated
- Seamless switchover between on and off-grid (4ms)

Safe & Reliable

- Up to 3 MPPTs with AFCI
- IP66 rated design

www.sofarsolar.com

© As of May 2026, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

System Parameters						
System Schematic						
Inverter Module	ESI-8/10/12K-S1					
Number of Inverter Modules	1					
Battery Module	BTS 5K					
Number of Battery Modules	1	2	3	4	5	6
Battery Total Energy [1]	5.12Wh	10.24Wh	15.36Wh	20.48Wh	25.6Wh	30.72kWh
IP Rating	IP66					
Operating Temperature Range [2]	-25˚C ~ +50˚C (derating above + 45˚C)					
Relative Humidity Range	5%-95%					
Max. Operating Altitude [3]	4000m (derating above 2000m)					
Weight	85kg	135kg	185kg	235kg	285kg	335kg
Dimension (W×H×D) [4]	708×920×170mm	708×1340×170mm	708×1760×170mm	708×1340×170mm 708×940×170mm	708×1340×170mm 708×1360×170mm	708×1760×170mm 708×1360×170mm
Base Dimensions (W×H×D)	620×60×170mm (floor installation), 620×310×170mm (wall-mounted installation)					
Display	LCD & APP					
Communication	CAN/RS485/WiFi, Optional: 4G/LAN					
Product Ordering Model	[ESI-8/10/12K-S1 Inverter Module] + N * [BTS 5K Battery Module]					

Inverter Module	ESI-8K-S1	ESI-10K-S1	ESI-12K-S1
PV Input			
Recommended Max. PV Power	16kWp	20kWp	24kWp
Max. Input Voltage	600Vd.c.		
Start-up Voltage[5]	90Vd.c.		
Rated Input Voltage	360Vd.c.		
MPPT Voltage Range	60-550Vd.c.		
Number of MPPT	1/1/1		
Max. Input Current	20/20/20A		
Max. Isc	25/25/25A		
Battery			
Voltage Range	120-576Vd.c.		
Max. Charging Current	50A		
Max. Discharging Current	50A		
AC Backup (Output)			
Rated Output Voltage	L+N+PE, 230Va.c.		
Rated Output Frequency	50/60Hz		
Rated Output Power	8kW	10kW	12kW
Max. Apparent Power	8.8kVA	11kVA	13.2kVA
Peak Output Apparent Power[6]	1.5 times of rated power, 10s		
Switching Time[7]	4ms default		
AC Grid (Input and Output)			
Rated Voltage	L+N+PE, 220/230/240Va.c.		
Rated Frequency	50/60Hz		
Rated Output Power	8kW	10kW	12kW
Max. Apparent Power	8.8kVA	11kVA	13.2kVA
Max. Output Current	38.3A	47.8A	57.4A
Max. Input Current	63A		
Power Factor Range	0.8 lagging - 0.8 leading		
General Parameter			
Dimensions (W×H×D) / Weight	708×440×170mm / 35kg		
Battery Module	**BTS 5K**		
Battery Type	$LiFePO_4$ - lithium iron phosphate battery		
Battery Module Energy[1]	5.12kWh		
Rated Power	2.5kW		
Topology	Isolation		
Dimensions (W×H×D) / Weight	708×420×170mm / 50kg		

[1] Test conditions: 0.2C charging/discharging at 25˚C, 100%DOD. [2] Please refer to the temperature derating curve.
[3] If the altitude is >2000m, derating is required. Please refer to the derating curve. [4] Dimensions of the inverter and batteries.
[5] Minimum PV voltage to start MPPT operation. [6]Full battery and sun. [7] In the on-grid mode, the nominal power of the hybrid inverter is higher than the total power of the home loads.

*All specifications are subject to change without notice.